



Compact A4 device offers optimal productivity

The imageRUNNER ADVANCE DX 619i offers both high printing and scanning speeds to busy workgroups, raising work productivity. With support for varied paper sizes and smart workflows, it is the ideal device for modern offices.

WORKFLOW EFFICIENCY

- Intuitive touchscreen provides users with smartphone-like usability, making navigation a breeze.
- Intelligent feeder allows effortless, rapid scanning with features like multi-sheet feed detection and skip blank originals.
- My ADVANCE enables a unique, personal experience tailored to meet each user's workflow needs. Settings, such as display language, initial log-in screen, and accessibility options, can be synchronised across multiple devices for consistency.
- Canon's MEAP platform provides process optimisation, by integrating with a range of powerful document, capture and output management solutions.
- Scalable support for mobile where users can connect directly to the device with Direct Access Point. Capture, scan or print documents easily with the Canon Print Business app.

COST MANAGEMENT

- The ability to apply print policies, monitor output, and restrict usage by user helps reduce unnecessary printing, resulting in lower total document cost.
- Tight integration with output management solutions, such as uniFLOW, provides the ability to carry out detailed tracking, reporting, and cost analysis.
- Quality and reliability, combined with remote diagnostics and assistance, can help reduce costs by minimising downtime and time spent by IT.
- Consistent user operation combined with remote and centralised fleet management can help simplify IT management of devices and entire fleets.

QUALITY AND RELIABILITY

- The new All-in-One cartridge makes replacement easy and convenient, increasing device uptime.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Canon's device management tools give you a centralised point of control across your entire fleet, upgrade devices remotely, check device and consumables status and capture meter readings.
- Standard PCL and Adobe PostScript print driver allows seamless integration with enterprise applications.
- Remote diagnostics allow timely, accurate and effective resolution.
- Intuitive user maintenance videos and status notifications available to help achieve maximum uptime and keep supplies replenished.

SUSTAINABILITY

- Combination of fusing technologies and low-melting-point toner help lowers overall electricity
- Minimise paper waste by holding jobs at the device with Force Hold Print. Choose to preview your print jobs or even change print settings at the device to achieve the desired results at the first time of printing.

SECURITY

- Control who has access to the device with different authentication methods such as picture login, department ID, user authentication and card access.
- Ensure information privacy and security across your network with IPsec, port filtering capabilities, and SSL technology.
- Enhance document confidentiality with encrypted secure print, secure print, secure watermark, encrypted PDF and device signature PDF.
- System verification at startup and McAfee® Embedded Control ensures device security, protecting against malware and tampering of firmware.
- Integrate with third-party solutions for complete monitoring protection.

MACHINE SPECIFICATION

MAIN UNIT

Type
A4 Monochrome Laser Multifunctional

Core Function
Print, Copy, Scan, Send, Store and Optional Fax

Processor
Canon Dual Custom Processor (Shared)

Control Panel
10.1" TFT LCD WSVGA Colour Touch Panel

Memory
RAM Main CPU: 2GB
Image Processing CPU: 1GB + 0.5GB

Hard Disk Drive
Standard: (SSD) 256GB

Interface Connection
Network
Standard : 1000Base-T/100Base-TX/10Base-T
Optional : Wireless LAN (IEEE 802.11 b/g/n)

Others
Standard : USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)
Optional : Copy Control Interface

Paper Supply Capacity (A4, 80gsm)
Standard : 650 sheets
100-sheets Multi-purpose tray x 1
550-sheets Paper cassette x 1
Maximum : 3,200 sheets
(with High Capacity Cassette Feeding Unit-D1)

Paper Output Capacity (A4, 80gsm)
500 sheets

Finishing Capabilities
Collate, Group

Supported Media Types
Multi-purpose tray:
Thin, Plain, Recycled, Heavy, Colour, Transparency, Bond,
Envelope

Paper Cassette:
Thin, Plain, Recycled, Heavy, Colour, Labels, Bond, Pre-punched

Supported Media Sizes
Multi-purpose tray:
Standard size : A4, A5, A5R, A6, B5
Custom size : 76.2 x 127.0 mm to 216.0 x 355.6 mm
Envelopes : COM10 No.10, Monarch, DL, ISO-C5
Paper Cassette:
Standard size : A4, A5, A5R, A6, B5
Custom size : 99.0 x 148.0 mm to 216.0 x 297.0 mm

Supported Media Weights
Multi-purpose tray : 60 to 200 gsm
Paper Cassette : 60 to 135 gsm
Duplex : 60 to 120 gsm

Warm-up Time
Quick Startup Mode : 4 Seconds or Less^{*1}
From Sleep Mode : 10 Seconds or Less
From Power On : 10 Seconds or Less^{*2}

^{*1} Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.
^{*2} Time from device power-on, until copy ready (not print reservation)

Dimensions (W x D x H)
500 x 598 x 617 mm

Installation Space (W x D)
1,052 x 823 mm
(with left CRG door opened + right door opened
+ cassette drawer opened)

Weight
Approx. 37 kg including toner

Print Specifications

Print Speed (BW, 1-sided)
Up to 61 ppm (A4)
Up to 99 ppm (A5)
Up to 35 ppm (A5R, A6)

Print Resolution (dpi) 600 x 600

Page Description Languages
Standard : UFR II, PCL6, Adobe PostScript 3

Direct Print
Supported File Types: TIFF, JPEG, PDF, EPS and XPS

Printing from mobile and cloud
AirPrint, Mopria, Canon PRINT Business,
uniFLOW Online and Universal Print

Fonts
PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT/J/K/S/T¹ (Japanese, Korean,
Simplified and Traditional Chinese), Barcode fonts^{*2}

^{*1} Requires optional PCL INTERNATIONAL FONT SET-A1
^{*2} Requires optional BARCODE PRINTING KIT-D1

Operating System
UFR II: Windows® 10/11/Server2012/Server2012 R2/
Server2016/Server2019/Server2022, Mac OS X(10.13 or later)
PCL: Windows® 10/11/Server2012/Server2012 R2/Server2016/
Server2019/Server2022
PS: Windows® 10/11/Server2012/Server2012 R2/Server2016/
Server2019/Server2022, Mac OS X(10.13 or later)
PPD: Windows® 10/11, Mac OS X(10.13 or later)

Copy Specifications

Copy Speed (BW, 1-sided)
Up to 61 ppm (A4)
Up to 99 ppm (A5)
Up to 35 ppm (A5R, A6)

First-Copy-Out Time (A4) Approx. 5.0 seconds or less

Copy Resolution (dpi) 600 x 600

Multiple Copies Up to 9,999 copies

Copy Density Automatic or Manual (9 Levels)

Magnification
Variable zoom: 25% to 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 70%, 81%, 86%,
100% (1:1), 115%, 122%, 141%, 200%, 400%

Scan Specifications

Standard Type
Single-pass Duplexing Automatic Document Feeder*
[2-sided to 2-sided (Automatic)]
* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80gsm)
Up to 100 Sheets

Acceptable Originals and Weights
Platen: Sheet, Book and 3-Dimensional Objects
Document Feeder media weights:
1-sided scanning: 42 to 128 gsm (BW), 64 to 128gsm (CL)
2-sided scanning: 50 to 128 gsm (BW), 64 to 128gsm (CL)

Note: Business card 80 to 220 gsm
Originals with width narrower than A6: 50 to 128 gsm

Supported Media Sizes
Platen scanning size: up to 216.0 x 355.6 mm
Document Feeder media size: A4, A5R, A6, B5
Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm
Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm

Scan Speed (ipm: BW and CL, A4)
Send (300 x 300 dpi): Automatic Colour Select "OFF":
1-sided Scanning : 95
2-sided Scanning : 190
Automatic Colour Select "ON":
1-sided Scanning : 50
2-sided Scanning : 100
Copy (600 x 600dpi): 1-sided Scanning : 95
2-sided Scanning : 140

Scan Resolution (dpi)
Scan for Copy : 600 x 600
Scan for Send : (Push) 600 x 600 (SMB/FTP/WebDAV/
IFAX), (Pull) 600 x 600
Scan for Fax : 600 x 600

Pull Scan Specification

Color Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows® 10/11/Server2012/Server2012 R2/
Server 2016/Server2019/Server2022

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP), SMB,
FTP, WebDAV, Mail Box
Optional: Super G3 FAX, IP Fax

Address Book

LDAP (2,000)/Local (1,600)/One-touch (200)

Send Resolution (dpi)

Push : up to 600 x 600
Pull : up to 600 x 600

Communication Protocol

File : FTP (TCP/IP), SMB 3.1.1 (TCP/IP), WebDAV
E-mail/Fax : SMTP, POP3

File Format

Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply
policy, Optimize for Web, PDF/A-1b, Trace &
Smooth, Encrypted, Device Signature,
User Signature), XPS(Compact, Searchable,
Device Signature, User Signature), Office
Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines 1

Modem Speed Super G3 : 33.6 kbps
G3 : 14.4 kbps

Compression Method MH, MR, MMR, JBIG

Resolution (dpi) 400x400 (Ultra Fine),
200x400 (Super Fine),
200x200 (Fine),
200x100 (Normal)

Sending/Receiving Size

Sending : A4, A5*, A6*, B5*

Receiving : A4, A5, B5

* Sent as A4

FAX Memory Up to 30,000 pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations Max. 199 dials

Sequential Broadcast Max. 256 addresses

Memory Backup Yes

Store Specifications

Mail Box (Number supported)
100 User Inboxes, 1 Memory RX Inbox,
50 Confidential Fax Inboxes
Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows® 10/11
Concurrent Connections (Max.): SMB: 64, WebDAV: 3

Advanced Box available disc space

Approx. 16GB

Security Specifications

Authentication

User Authentication: Picture Login, Picture and PIN Login,
Card Login, Username and Password Login, Function Level
Login, Mobile Login

Department ID Authentication: Department ID and PIN
Login, Function Level Login

uniFLOW Online Express: PIN Login, Picture Login, Picture
and PIN Login, Card Login, Card and PIN Login, Username
and Password Login, Department ID and PIN Login,
Function Level Login

Access Management System: Access Control

Document Security

Print Security: Secure Print, Encrypted Secure Print, Forced
Hold Printing, uniFLOW Secure Print*

Receive Data Security: Confidential Fax Inboxes Forwarding
Received Documents Automatically

Scan Security: Encrypted PDF, Device Signature PDF/
XPS, User Signature PDF/XPS, Adobe LiveCycle Rights
Management ES2.5 Integration

BOX Security: Mail Box Password Protected, Advanced Box
Access Control

Send Data Security: Setting for requesting password input
per transmission, Restricted E-mail/File send functions,
Confirming FAX number, Allow/Restrict Fax Driver
Transmissions, Allow/Restrict Sending from History, S/MIME
Support

Document Tracking: Secure Watermark

* Requires uniFLOW Online/uniFLOW

Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0,
Firewall Functionality (IP/MAC Address Filtering), Dual
Network Support (Wired LAN/Wireless LAN, Wired LAN/
Wired LAN), Disabling Unused Functions (Enabling/
Disabling Protocols/Applications, Enabling/Disabling
Remote UI, Enabling/Disabling USB Interface), G3 FAX
separation from LAN, USB Port separation from LAN,
Prohibit the execution of files stored in Advanced Box in the
MFP, Scan and Send -Virus Concerns for E-mail Reception

Device Security

Protecting SSD Data (SSD Data Encryption (FIPS140-2
Validated, SSD Lock), SSD Data Overwrite Erase, SSD Lock),
Standard SSD Initialize, Trusted Platform Module (TPM), Job
Log Conceal Function, Checking MFP Software Integrity
(Verify System at Startup, Runtime Intrusion Detection),
Common Criteria Certification (HCD-PP) (pending
confirmation)

Device Management and Auditing

Administrator Password, Digital Certificate And Key
Management, Audit Log, Cooperating with External
Security Audit System (Security Information and Event
Management), Image Data Logging, Security Policy Setting

Environment Specifications

Operating Environment

Temperature: 10 to 30 °C
Humidity: 20 to 80 % RH (Relative Humidity)

Power Requirements

Power Source: 220-240 V, 50/60 Hz, 4.8 A

Power Consumption

Maximum: Approx. 1,500 W

Consumables

Toner T03 Black

Toner Yield

Black: 51,500 pages
Toner Cartridge yield in accordance with
ISO/IEC 19752

Software and Printer Management

Tracking and reporting

uniFLOW Online Express/uniFLOW Online

Remote Management Tools

iW Enterprise Management Console
eMaintenance
Content Delivery System

Scanning Software

Color Network ScanGear 2

Optimisation Tools

Canon Driver Configuration Tool

Platform

MEAP (Multifunctional Embedded Application Platform)

Document Publishing

IW DESKTOP

Paper Supply Options

Cassette Module-AG1

Paper Capacity : 550 Sheets (80gsm)
Paper Type : Thin, Plain, Recycled, Heavy, Colour,
Labels, Bond, Pre-punched
Paper Size : A4, A5, A5R, A6, B5
Custom Size : 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight : 60 to 135 gsm
Power Source : From the Main Unit
Dimensions : 484 mm x 450 mm x 150 mm
(W x D x H) (attached to the main unit)
Weight : Approx. 7 kg

Cassette Feeding Unit-AR1

Paper Capacity : 550 Sheets (80gsm)
Paper Type : Thin, Plain, Recycled, Heavy, Colour,
Labels, Bond, Pre-punched
Paper Size : A4, A5, A5R, A6, B5
Custom Size : 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight : 60 to 135 gsm
Power Source : From the Main Unit
Dimensions : 642 mm x 657 mm x 479 mm
(W x D x H) (attached to the main unit)
Weight : Approx. 19 kg

High Capacity Cassette Feeding Unit-D1

Upper cassette:

Paper Capacity : 550 sheets (80 gsm)
Paper Type : Thin, Plain, Recycled, Heavy, Colour,
Labels, Bond, Pre-punched
Paper Size : A4, A5, A5R, A6, B5
Custom size : 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight : 60 to 135 gsm

Lower cassette:

Paper Capacity : 2,000 sheets (80 gsm)
Paper Type : Thin, Plain, Recycled, Heavy, Colour, Bond,
Pre-punched
Paper Size : A4
Paper Weight : 60 to 135 gsm
Power Source : From the Main Unit
Dimensions : 642 x 657 x 479 mm
(W x D x H) (attached to the main unit)
Weight : Approx. 27 kg

Cassette Feeding Unit-AX1

Paper Capacity : 1st Cassette 550 sheets (80gsm)
2nd cassette 550 sheets (80gsm)
3rd cassette 550 sheets (80gsm)
Paper Type : Thin, Plain, Recycled, Heavy, Colour,
Labels, Bond, Pre-punched
Paper Size : A4, A5, A5R, A6, B5,
Custom size: 99.0 x 148.0 mm to
216.0 x 355.6 mm
Paper Weight : 60 to 135 gsm
Power Source : From the Main Unit
Dimensions : 642 x 657 x 479 mm
(W x D x H) (attached to the main unit)
Weight : Approx. 27kg

System and Controller Options

Print Accessories

PCL INTERNATIONAL FONT SET-A1
PCL ASIAN FONT SET-A1
BARCODE PRINTING KIT-D1

FAX Accessories

SUPER G3 FAX BOARD-BM1
REMOTE FAX KIT-A1
IP FAX EXPANSION KIT-B1

Interface Accessories

WIRELESS LAN BOARD-D1
COPY CONTROL INTERFACE KIT-A1

Other Options

Accessibility Accessories

ADF ACCESS HANDLE-A1

Staple Cartridges

STAPLE-P1

For full specifications, please refer to the specification
table on your local Canon web site.

MAIN CONFIGURATION OPTIONS

iR-ADV DX 619i



CASSETTE FEEDING UNIT-AR1

- Supports up to A4
- Media weight 60–135 gsm
- 550 sheets (80 gsm)
- Floor standing



CASSETTE FEEDING UNIT-AX1

- Supports up to A4
- Media weight 60–135 gsm
- 3 x 550 sheets (80 gsm)
- Floor Standing



HIGH CAPACITY CASSETTE FEEDING UNIT-D1

- Supports up to A4
- Media weight 60–135 gsm
- 1 x 550 sheets and 1 x 2,000 sheets (80 gsm)
- Floor standing



CASSETTE MODULE-AG1

- Supports up to A4
- Media weight 60–135 gsm
- 550 sheets (80 gsm)
- Desktop

Partner/Dealer Stamp



Adobe PostScript

To arrange for a demonstration, simply contact our offices below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageRUNNER ADVANCE, MEAP, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is independent party software distributed by Canon Singapore Pte Ltd.

Adobe, LiveCycle, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2023 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.