


# Refillable Monochrome Ink Tank for High Volume Printing



## Perfect for Businesses with Heavy Print Requirements

- Print, Scan, Copy, Fax
- Auto Duplex Printing
- ID card copying
- Borderless photo printing (up to A4)
- Wireless/Wired LAN, Direct Wireless
- Mobile & Cloud Printing



**LARGE PAPER  
CAPACITY FOR MORE  
CONVENIENCE**  
(Load up to 350 sheets)



**35 SHEETS AUTO  
DOCUMENT FEEDER**



**FAST, NO-MESS  
INK FILLING**

SPECIFICATIONS: G7070				
PRINT	Maximum Printing Resolution*1		4800 (horizontal) x 1200 (vertical) dpi	
	Number of Ink Bottles		4	
	Print Speed*2 (approx.)	Document: B&W / Colour	ESAT / Simplex	13.0 ipm / 6.8 ipm
		Photo (4 x 6")	PP-201 / Borderless	45 sec
	Paper Handling	Input Capacity		Cassette / Rear Tray Up to 250 sheets / 100 sheets
		Paper Size	Cassette	A4, A5, B5, LTR, Custom (148 x 210 to 215.9 x 297 mm)
			Rear Tray	A4, A5, B5, LTR, LGL, 4 x 6", 5 x 7", 7 x 10", 8 x 10", Envelope (DL, COM10), Square (5 x 5", 3.5 x 3.5", 89 x 89 mm), Card Size (91 x 55 mm), Custom (55 x 89 to 215.9 x 676 mm)
			Borderless Printing*3	Up to A4
		Auto Duplex Printing		A4, A5, B5, LTR (Plain Paper)
		Paper Type (Supported)	Cassette	Plain Paper (64-105 g/m <sup>2</sup> )
Rear Tray	Plain Paper (64-105 g/m <sup>2</sup> ) High Resolution Paper (HR-101N) Photo Paper Pro Platinum (PT-101) Photo Paper Pro Luster (LU-101) Photo Paper Plus Glossy II (PP-201) Matte Photo Paper (MP-101) Double Side Matte Paper (MP-101D) Glossy Photo Paper "Everyday Use" (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Plus Glossy II (PP-208) Photo Stickers (PS-108/PS-208/PS-808) Removable Photo Stickers (PS-308R) Magnetic Photo Paper (PS-508) Dark Fabric Iron-On Transfer (DF-101) Envelope			
SCAN*4	Scanner Type / Scanning Method		Flatbed & ADF / CIS (Contact Image Sensor)	
	Optical Resolution*5		1200 x 2400 dpi	
COPY	Maximum Document Size		A4 / Letter (216 x 297 mm)	
	Copy Speed*6 (approx.)	Colour Document	sFCOT / Simplex 22 sec	
		Document (ADF)	sESAT / Simplex 3.9 ipm	
	Multiple Copy (max.)	B&W / Colour	ESAT / Simplex 4.3 ipm	
FAX	Transmission Speed*7 (approx.)	B&W / Colour	99 pages	
	Transmission / Reception Memory*8 (approx.)		3 sec / 1 min (33.6 kbps)	
	PC Fax		50 pages	
	Automatic Group Dialing (max.)		Windows / Mac: Available	
NETWORK / SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS	Windows		19 locations	
	Macintosh		Windows 10/8.1/7 SP1*9	
	Operational Panel	Please visit <a href="https://asia.canon">https://asia.canon</a> to confirm OS compatibility and to download the latest driver	OS X 10.11, macOS 10.12 ~ 10.14	
	Interface		2-Line LCD	
	Mobile Printing Applications		Wireless LAN IEEE802.11b/g/n, 100 Base-TX/10 Base-T, USB 2.0	
	Other Connectivity Features		Creative Park, Canon PRINT, Easy-PhotoPrint Editor	
	Recommended Monthly Print Volume		Mopria® Certified, AirPrint™, Google Cloud Print™, Cloud Service, Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Wireless / Wired LAN PictBridge, Direct Wireless	
	Power Consumption (approx.)		150 - 1,500 pages	
	Dimensions (W x D x H) (approx.)		15W (1.0 W Standby)	
	Weight (approx.)		403 x 369 x 234 mm	
PAGE YIELD*10	Plain Paper	9.6 kg	A4 Colour Documents*11: GI-70 PGBK: 6,000 (Economy Mode*12: 8,300) GI-70 C, M, Y: 7,700	
	Photo Paper (PP-201)		4 x 6" Photos*13: GI-70 PGBK: NA GI-70 C, M, Y: 2,200	

Specifications are subject to change without notice.

\*1 Ink droplets can be placed with a pitch of 1/4800 inch at minimum.

\*2 Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.

\*3 Paper types NOT supported for borderless printing are as follows: Envelope, High Resolution Paper, T-Shirt Transfer, Photo Stickers

\*4 TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.

\*5 Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard.

\*6 Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183.

Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735.

Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warming up time.

\*7 Black & white document fax transmission speed is based on default setting using ITU-T No.1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.

\*8 Page count is based on ITU-T No.1 chart or Canon FAX Standard Chart No.1.

\*9 Operation can only be guaranteed on pre-installed Windows 7 or later.

\*10 Page yields may vary depending on content coverage, print settings, temperature, humidity, and frequency of printing.

\*11 Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart and continuous printing simulation with the replacement ink bottles after initial setup. The colour yield is based on 1 set of composite colour bottles.

\*12 The Economy mode reduces the ink consumption by lowering the density. More pages can be printed using this mode.

\*13 Declared yield value is the estimated value based on Canon individual test method using the ISO/IEC 29103 chart and continuous printing simulation with the replacement ink bottles after initial setup. Black ink is not used when printing under this condition. However, a minimal amount of black ink is used for maintenance purposes.