

imageFORCE 4100 series

Canon

Delighting You Always

Powering High-Volume Productivity



Built for robust monochrome printing, the **imageFORCE 4100 Series** provide high-speed print performance with high paper capacity to meet the demands of large volume print jobs.

Scanning comes at a fast scan speed of up to 270 ipm, with feeder options to handle the scanning of business card to full A3 document.

Powered with Security Environment Estimation Technology, it recommends the right security settings to help keep your business secure with confidence.



CONNECTIVITY

Scan to and print from cloud platforms like Google Drive and Dropbox. Print from your mobile with Canon PRINT, AirPrint, Mopria and more for maximum convenience.



RELIABILITY

Flexible configuration options adapt seamlessly to varying print capacities and scanning needs, helping to boost efficiency while reducing downtime.



SECURITY

Robust security features ensure comprehensive protection to your print data. From authentication, document security to network and device security, enjoy a peace of mind on safeguarding any sensitive documents at all times.



SUSTAINABILITY

Engineered with up to 30% of post-consumer recycled plastic and up to 5% of recycled steel, meeting your sustainability commitments without compromise.

Business Can Be Simple

imageFORCE 4100 series

Main Unit

Machine Type

A3 Monochrome Multifunctional

Processor

Dual Core Processor

Core Functions

Print, Copy, Scan, Send, Store and Optional Fax

Control Panel

10.1-inch TFT LCD WSVGA Colour Touch Panel

Memory

Standard: RAM 5.0 GB

Storage

Standard: (SSD) 256 GB

Optional: (SSD) 1 TB

Interface Connection

Network:

Standard: 1000Base-T/100Base-TX/10Base-T

Optional: Wireless LAN (IEEE 802.11 a/b/g/n/ac/ax)

Others:

Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1,
USB 2.0 (Device) x1

Optional: Serial Interface

Paper Supply Capacity (A4, 80 gsm)

Standard: 1,200 sheets

100 sheets: Multi-purpose tray x1

550 sheets: Standard Cassette x2

Maximum: 6,350 sheets (with High Capacity Cassette
Feeding Unit-G1 + Paper Deck Unit-F3)

Paper Output Capacity (A4, 80 gsm)

Standard: 250 sheets

Maximum: 3,450 sheets (with Staple Finisher-AH1 or
Booklet Finisher-AH1 and Copy Tray-T2)

Supported Media Types

Multi-purpose Tray:

Thin, Plain, Recycled, Colour, Heavy, Coated*, Tracing,
Bond, Transparency, Labels, Pre-punched,
Letterhead, Envelope

*257-300 gsm requires Media Adjustment Kit-A1

Upper Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency,
Pre-punched, Letterhead, Envelope*

*Envelope Feeder Attachment B (standard) is required
except ISO-C5

Lower Cassette:

Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency,
Pre-punched, Letterhead, Envelope*

*Envelope Feeder Attachment A (standard) is required

Supported Media Sizes

Multi-purpose Tray:

Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4,
B5, B5R

Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm

Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm

Envelopes: COM10 No.10, Monarch, ISO-C5, DL

Envelope custom size: 98.0 x 98.0 mm to
320.0 x 457.2 mm

Upper Cassette:

Standard size: A4, A5, A5R, A6R, B5

Custom size: 105.0 x 148.0 mm to 297.0 x 215.9 mm

Envelopes: ISO-C5

Lower Cassette:

Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R

Custom size: 105.0 x 148.0 mm to 304.8 x 457.2 mm

Envelopes*: COM10 No.10, Monarch, DL

*Envelope Feeder Attachment A (standard) is required

Supported Media Weight

Multi-purpose Tray:

52 to 300 gsm (Only 60 to 300 gsm supported with
Media Adjustment Kit-A1*)

*Media Adjustment Kit-A1 is required for Coated
(257-300 gsm)

Upper/Lower Cassette:

52 to 256 gsm

Duplex:

52 to 256 gsm

Warm-up Time (Quick Start Mode: ON)

Quick Startup Mode: 4 seconds or less*

*Time from device power-on to when the copy icon
appears and is enabled to operate on the touch panel
display

From Power On: 10 seconds or less*

*Time from device power-on, until copy ready (not print
reservation)

From Sleep Mode: 10 seconds or less

Dimensions (W x D x H)

With Platen Cover-Y3: 565 x 745 x 788 mm

With Single Pass DADF-E1: 565 x 745 x 897 mm

With Single Pass DADF-F1: 565 x 745 x 862 mm

Installation Space (W x D)

Basic: 978 x 1,141 mm (right door & multi-purpose tray
opened + paper cassette opened)

Fully Configured: 1,806 x 1,141 mm (with Single Pass
DADF-E1/F1 + Staple Finisher-AH1/
Booklet Finisher-AH1 + Paper Deck
Unit-F3 + paper cassette open)

Weight Including Regular Toner

With Platen Cover-Y3: Approx. 66 kg

With Single Pass DADF-E1: Approx. 80 kg

With Single Pass DADF-F1: Approx. 73 kg

Print Specifications

Print Speed (BW and CL)

imageFORCE 4145:

1-sided: Up to 45 ppm (A4), Up to 22 ppm (A3),
Up to 32 ppm (A4R)

2-sided: Up to 45 ppm (A4), Up to 22 ppm (A3),
Up to 32 ppm (A4R)

imageFORCE 4135:

1-sided: Up to 35 ppm (A4), Up to 17 ppm (A3),
Up to 23 ppm (A4R)

2-sided: Up to 35 ppm (A4), Up to 17 ppm (A3),
Up to 23 ppm (A4R)

imageFORCE 4125:

1-sided: Up to 25 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

2-sided: Up to 25 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

Print Resolution (dpi)

4800 x 2400 dpi

Page Description Languages

Standard: UFR II, PCL6/PCL5

Optional: Adobe PostScript 3

Direct Print

PDF, EPS, TIFF/JPEG, XPS

Printing from Mobile and Cloud

AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW
Online, and Universal Print

OS Standard Printing

Android, Windows® 11, Chrome OS, macOS (11.2.2 or
later), iOS (15.2 or later), iPadOS

Operating System

UFR II: Windows® 11/Server2016/Server2019/
Server2022/Server2025, macOS (11.7 or later)

PCL: Windows® 11/Server2016/Server2019/
Server2022/Server2025

PS: Windows®11/Server2016/Server2019/Server2022/
Server2025, macOS (11.7 or later)

PPD: Windows® 11, macOS (11.7 or later)

As of Mar 2026

Copy Specifications

Copy Speed (BW and CL)

imageFORCE 4145:

1-sided: Up to 45 ppm (A4), Up to 22 ppm (A3),
Up to 32 ppm (A4R)

2-sided: Up to 45 ppm (A4), Up to 22 ppm (A3),
Up to 32 ppm (A4R)

imageFORCE 4135:

1-sided: Up to 35 ppm (A4), Up to 17 ppm (A3),
Up to 23 ppm (A4R)

2-sided: Up to 35 ppm (A4), Up to 17 ppm (A3),
Up to 23 ppm (A4R)

imageFORCE 4125:

1-sided: Up to 25 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

2-sided: Up to 25 ppm (A4), Up to 15 ppm (A3),
Up to 20 ppm (A4R)

First-Copy-Out Time (A4, BW/CL)

imageFORCE 4145: 4.6 seconds

imageFORCE 4135: 5.5 seconds

imageFORCE 4125: 6.1 seconds

Copy Resolution (dpi)

600 x 600 dpi

Multiple Copies

Up to 9,999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25 % to 400 % (1 % increments)

imageFORCE 4100 series

Scan Specifications

Type

Standard: Colour Platen
Optional: Platen Cover-Y3, Single Pass DADF-E1* or Single Pass DADF-F1* [2-sided to 2-sided (Automatic with DADF)]

DADF: Duplexing Automatic Document Feeder
**Multi-Sheet Feed Detection is supported*

Document Feeder Paper Capacity (80 gsm)

Single Pass DADF-E1: Up to 200 Sheets
Single Pass DADF-F1: Up to 100 Sheets

Document Feeder Acceptable Paper Weight

Document Feeder media weight:
Single Pass DADF-E1:
1-sided scanning: 38 to 220 gsm
2-sided scanning: 38 to 220 gsm
An acceptable weight of A6R or smaller is 50 to 220 gsm

Single Pass DADF-F1:
1-sided scanning: 38 to 128 gsm
2-sided scanning: 50 to 128 gsm

Supported Media Sizes

Platen: Max. scanning size: 297.0 x 431.8 mm

Single Pass DADF-E1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R

Custom size: 69.9 x 139.7 mm to 304.8 x 431.8 mm

Single Pass DADF-F1: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R

Custom size: 48.0 x 85.0 mm to 304.8 x 431.8 mm

Scan Resolution (dpi)

600 x 600 dpi

Scan Speed (ipm: BW/CL, A4)

Single Pass DADF-E1:

1-sided scanning: 135/135 (300 x 300 dpi, send), 80/- (600 x 600 dpi, copy)

2-sided scanning: 270/270 (300 x 300 dpi, send), 160/- (600 x 600 dpi, copy)

Single Pass DADF-F1:

1-sided scanning: 80/80 (300 x 300 dpi, send), 60/- (600 x 600 dpi, copy)

2-sided scanning: 120/120 (300 x 300 dpi, send), 60/- (600 x 600 dpi, copy)

Pull Scan Specifications

Color Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows® 11/Server 2016/ Server 2019/Server 2022/Server 2025*

**As of Mar 2026*

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP*), SMB, FTP, SFTP, WebDAV, Mail Box
Optional: Super G3 FAX, IP Fax
**Available OAuth 2.0 authentication method on Microsoft Exchange Online and Google Workspace*

Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

Communication Protocol

File: FTP (TCP/IP), SFTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV
E-mail/iFax: SMTP (send), POP3 (receive)

File Format

TIFF (MMR), JPEG*, PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, PDF/A-1a, PDF/A-2a, PDF/A-2b, PDF/A-2u, PDF/A-3a, PDF/A-3b, PDF/A-3u, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
**Single-page only*

Fax Specifications

Maximum Number of Connection Lines

4

Modem Speed

Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 dpi (Ultra Fine), 200 x 400 dpi (Super Fine), 200 x 200 dpi (Fine), 200 x 100 dpi (Normal)

Sending/Receiving Size

Sending: A3, A4, A4R, A5¹, A5R¹, A6R¹, B4, B5², B5R¹

Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R

¹Sent as A4

²Sent as B4 short

FAX Memory

Up to 30,000 pages (2,000 jobs)

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 dials

Sequential Broadcast

Max. 256 addresses

Memory Backup

Yes

Store Specifications

Mail Box (Number Supported)

100 User Inboxes
1 Memory RX Inbox
50 Confidential Fax Inboxes
Maximum 30,000 Pages (2,000 jobs) Stored

Advanced Box

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows® 11*
Concurrent Connections (Max.): SMB:64, WebDAV:3
**Windows 11 only supports SMB*

As of Mar 2026

Advanced Box Available Disc Space

Standard: 16 GB (With option: max. 480 GB)

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C
Humidity: 20 to 80 % RH (Relative Humidity)

Power Source

220-240V, 50/60Hz, 5A

Power Consumption

Maximum: Approx. 1,500W
Sleep Mode: Approx. 0.5W*
**0.5W is not available in all circumstances due to certain settings*

Consumables

Toner Cartridges

NPG-1010 Toner Bk

Toner (Estimated Yield @ 6 % Coverage)

NPG-1010 Toner BK: 42,000 pages

Configuration Output Options*



Booklet Finisher-AH1

- 2-tray, up to 3,250-sheet capacity
- Corner and double staple up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and non-staple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 10 sheets (80 gsm)
- Supports optional external 2/3 Hole Puncher Unit-A1 and 2/4 Hole Puncher Unit-A1



Staple Finisher-AH1

- 2-tray, up to 3,250-sheet capacity
- Corner and double staple up to 50 sheets (80 gsm)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 50 sheets (80 gsm)
- Supports optional external 2/3 Hole Puncher Unit-A1 and 2/4 Hole Puncher Unit-A1



SP DADF-E1

- Multiple document scanning
- 200 sheet duplexing automatic document feeder
- Scans up to 135 ipm (1-sided, 300 dpi) and 270 ipm (2-sided, 300 dpi)



SP DADF-F1

- Multiple document scanning
- 100 sheet duplexing automatic document feeder
- Scans up to 80 ipm (1-sided, 300 dpi) and 120 ipm (2-sided, 300 dpi)



Platen Cover-Y3

- Single document scanning



Inner 2 Way Tray-M1

- Separates copies, prints and faxes
- Adds a second internal output tray



Inner Finisher-N1

- 2-tray, 545-sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports ECO-Staple 8 sheets (80 gsm) and Staple-On-Demand 40 sheets (80 gsm)



Utility Tray-B1



Copy Tray-T2



Paper Deck Unit F3

- Supports up to A4
- Media weight 52-105 gsm
- 2,700 sheets (80 gsm)



imageFORCE PEDESTAL 31

- Raises the device, no additional media supply



Cassette Feeding Unit-BB1

- Supports up to A3
- Media weight 52-256 gsm
- 2 x 550 sheets (80 gsm)



High Capacity Cassette Feeding Unit-G1

- Supports A4
- Media weight 52-256 gsm
- 2,450 sheets (80 gsm)

*Paper capacity may vary with different paper type/size.



Partner / Dealer Stamp

To arrange for a demonstration, simply contact our office below.

**SOUTH & SOUTHEAST ASIA
REGIONAL HEADQUARTERS**

Canon Singapore Pte. Ltd. | 1 Fusionopolis Place #14-10 Galaxis Singapore 138522
Tel: 65-6799 8888 | Fax: 65-6799-8882 | <https://asia.canon/> | <https://sg.canon/>

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximate. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

Canon, imageFORCE, MEAP, eMaintenance, iW and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. "MEAP" is a trademark of CANON Inc., referring to an "application platform" for Canon multifunction and single function printers. Other names may be the trademarks of their respective owners. uniFLOW is an independent party software distributed by Canon Singapore Pte Ltd.

Adobe, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe in the United States and/or other countries.

2026 Canon Singapore Pte. Ltd.
All rights reserved. Printed in Singapore.