


JustPerfect.

Limitless Creativity Made Possible























The new 24" **imagePROGRAF TM-5255** and **TM-5250** large format printers raise the standard for print excellence through greater business printing performance for creating photo images, posters and CAD drawings. Express limitless creativity through vivid, quality prints thanks to improved ink capabilities.

High-Quality Printing For Everything Creative

Create vivid, high-quality photos and posters with the new 24" imagePROGRAF TM-5255 and TM-5250 large format printers. The improved ink capabilities help to bring out greater colour expressions within prints, while catering to the needs of engineering firms by offering multi-application printing suited for limitless creativity.



Greater Productivity with Swiftness

Experience enhanced printing productivity with the new L-COA PRO II high-speed imaging processing chip, which provides greater data processing power that ensures quicker turnaround times from sleep mode alongside continuous printing with ease.





Based on Canon internal testing using plain paper with continuous printing of A1 page per min

Print Borderless

The TM-5250 and TM-5255 allow for borderless poster printing on any size of roll paper with ease.

Vivid Red for Greater Details

The **new magenta ink** offers a more vivid red that enhances the details on printed photo images, posters and CAD drawings produced by the printer.






TM-5250

Designed for Convenience

The printer's **flat top space** allows for effortless roll paper replacement or the placement of output prints.



Roll paper balance and paper media details can also be easily retrieved from the printer through **automatic** paper type detection.



Improved Scanning for Productivity

The printers can be used alongside a scanner that features new functions, such as a **maximum paper thickness of 0.8mm** alongside **brand new transparent guides** that enhance scanning productivity and operability overall.




TM-5250 MFP Lm24

Managing Workflows with Ease

Streamline how you manage workflows with convenient and intuitive software applications.

Direct Print Plus

Direct Print Plus offers **easy batch printing of PDF and JPEG files** with custom templates.



Accounting Manager

The Accounting Manager feature offers greater convenience in **monitoring print usage**.



Free Layout Plus

Free Layout Plus provides for easy document resizing to specific paper layouts before printing by simply dragging and dropping files into the application.



PosterArtist

Design and **create visually appealing posters** effortlessly using the PosterArtist feature.



Check it out at https://posterartist.canon

SPECIFICATIONS

PRINTER	ICATIO	TM-5250	TM-5255		
Printer Type		5-Cold	ur, 24"		
Number of Nozzles		15,360 nozzles (MBK 5,120 nozzles, Other Colours 2,560 nozzles each)			
Max. Print Resolut	tion	2,400 x 1,200 dpi			
Nozzle Pitch		1,200 dpi × 2			
Line Accuracy*1		± 0.1 % or less			
	Sales Ink	130 ml / 300 ml (MBK, BK, C, M, Y)			
Ink Tank Size	Bundle Starter Ink	130 ml (MBK) / 90 ml (BK, C, M, Y)			
Ink Type		Pigment Ink			
Print Languages		HP-GL/2 JPEG (Ver	SG Raster (Swift Graphic Raster) HP-GL/2, HP RTL JPEG (Ver. JFIF1.02) CALS G4 ²		
		N/A PDF			
Print Solutions & Applications		Printer Driver (Win/Mac versions), Direct Print Plus, Free Layout PLUS, PosterArtist Windows Web & Lite, Wi-Fi Connection Assistant, PIXMA Cloud Link, Apple AirPrint (Mobile), Canon PRINT Inkjet/SELPHY (Mobile), Canon Print System (Mobile), uniFlow server			
Management Solutions		Media Configuration Tool (includes Color Customisation Tool), Accounting Manager, Device Management Console, Quick Utility Toolbox			
Interface (Built-In)	USB B Port	Hi-Speed USB, Full Speed (12 Mbit/sec), Hi-Speed (480 Mbit/sec), Bulk Transfer, Series B (4 pins)			
	USB A Port	N/A	USB Memory (Dire Supported file fo JPEG/PDF	ct Print) rmat:	
	Network	IEEE 802.3 10base-T IEEE 802.34 100base-T IEEE 802.35 1000base-T IEEE 802.35 Full Duplex SNMP, HTTP, TCP/PI (IPV4/IFV6), FTP			
	Wireless LAN	IEEE802.11 b/g/n WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES) WPA3-SAE (AES) WPA-SAE (AES) WPA-EAP (AES)'3 WPA2-EAP (AES)'3 WPA2-EAP (AES)'3			
Memory Hard Disk		2 GB No Hard Disk	128 GB (Physi Memory 2 GI 500 GB (Encryp Hard disk	B)	
Display		LCD (4.3 inch / 10	I.9 cm TFT color)		
OS Compatability	Please visit https://asia. canon to confirm OS compatibility and to download the latest drivers.	Windows, Macintosh			
SCANNER					
Scanner Model		Lm24			
Scan Width		24"			
Optical Resolution (DPI)		Up to 600 dpi			
Scan Format		TIFF, TIFF G4, PDF, PDF/A, JPEG Multipage PDF & JPEG			
Scan Destinations	•	Scan to PC, USB			
Scanner Software		ScanAPP			
Max. Copy Speed: (inch/sec) or (mm/sec)		Colour Draft (300/300 dpi): 1.5 ips / 38.1 mm per sec Standard (300/600 dpi): 1 ips / 25.4 mm per sec Best (600/600 dpi): 0.5 ips / 12.7 mm per sec Monochrome Draft (300/300 dpi): 4.5 ips / 11.4 mm per sec Standard (300/600 dpi): 3 ips / 76.2 mm per sec Best (600/600 dpi):	N/A		
Max. Scan Speed: (inch/sec) or (mm/sec)		Colour Draft (200 dpi): 1.5 ips / 38.1 mm per sec Colour Draft (200 dpi): 1.5 ips / 38.1 mm per sec Standard (300 dpi): 1.0 ips / 25.4 mm per sec Best (600 dpi): 0.5 ips / 12.7 mm per sec Monochrome Draft (200 dpi): 4.5 ips / 114.3 mm per sec Standard (300 dpi): 3.0 ips / 76.2 mm per sec Best (600 dpi): 1.5 ips / 38.1 mm per sec			
Maximum Original Thickness & Length		Up to 0.8 mm			
I III CKIIC 35 & Leng		I.			

PRINT SPEED*4		TM-5250	TM-5255	
Plain Paper	CAD Drawing (A1 Portrait, Fast Q5 mode)	20 sec		
Heavyweight Coated Paper	Poster (A1 Portrait, Standard mode)	1 min 23 sec		
MEDIA HANDLING				
Media Width	Roll Paper	203.2 ~ 610 mm		
Media Thickness	Roll Paper/ Cut Sheet	0.07 ~ 0.8 mm		
Printable Media	Roll Paper	203.2 mm ~ 18 m ¹⁵		
Length	Cut Sheet	279.4 ~ 1,600 mm		
Media Core Size		2 inch / 3 inch core		
Outside Diameter Roll Paper		150 mm or less		
Media Feed	Roll Paper	1 Roll, Top Load, Front Output		
	Cut Sheet	Front Load, Front Output		
Delivery Direction		Face-up, Front side		
Margins (Top, Bottom, Side)	Recommended Area (Roll Paper)	20 mm, 3 mm, 3 mm		
	Recommended Area (Cut Sheet)	20 mm, 20 mm, 3 mm		
	Printable Area (Roll Paper)	3 mm, 3 mm		
	Printable Area (Roll Paper Borderless Print)	0 mm		
	Printable Area (Cut Sheet)	3 mm, 20 mm, 3 mm		
DIMENSIONS (Wx	DxH) & WEIGHT*6			
Packaged Dimensions & Weight	Printer (Main unit + Pallet)	1,152 x 913 x 679 mm Weight: 73 kg		
	Stand + Basket (SD-26)	1,058 x 826 x 270 mm Weight: 22 kg		
	Printer (Main unit with stand and pallet) (SD-26)	1,152 x 913 x 946 mm Weight: 96 kg		
Printer & Weight	Printer	978 x 748 x 439 mm (Operation panel is not tilt up) Weight: 42 kg (excluding print head and ink)		
	Printer with Stand + Basket (SD-26)	978 x 885 x 1,060 mm (Basket Opened) 982 x 756 x 1,060 mm (Basket Closed) Weight: 55 kg (excluding print head and ink)		
Scanner & Weight		935 x 253 x 131 mm Weight: 5.28 kg	N/A	
POWER AND OPERATING REQUIREM				
Power Supply (Printer) AC 100 - 240 V (50 - 60 Hz)				
	Print Operation	Operation: < 62 W	Operation: < 64 W	
Power Consumption	Sleep Mode	<1.6	W	
(Printer)	Power OFF	< 0.1 W		
Recommended Environment Acoustic	Temperature	Temperature: 15 - 30 °C		
	Humidity	Humidity: 10 - 80 % RH (no dew condensation)		
	Power*7	Approx. 6.2 Bels		
	Pressure*7	Approx. 41 dB(A), Standby 35 dB(A) or less		
OPTIONAL ACCES	SORIES			
Roll Unit		-		
2/3" Roll Holder		RH2-28		
Printer Stand + Basket		SD-26		
Card Reader Interface for uniFLOW		RA-02		
CONSUMABLES				
Ink Tank		Magenta: PFI-8121 (130 ml) / PFI-8321 (300 ml) Matte Black / Black / Cyan / Yellow: PFI-8120 (130 ml) / PFI-8320 (300 ml)		
Print Head		PF-06		
Cutter Blade		CT-08		
Maintenance Cartridge		MC-31		

Specifications are subject to change without notice.

- "I User adjustments required. Printing environment and media must match those used for the adjustments. Paper required: Plain paper and coated paper only.
- $\ensuremath{^{^{\circ 2}}}\xspace$ USB Thumb drive printing is not supported.
- *3 IEEE802.1X (EAP-TLS/EAP-TTLS/PEAP) Supported.
- *4 Time taken to print one page does not include time required for data processing, data transfer and pre-printing operations.
- *5 Varies according to the OS and application.
- *6 Include roll holder set.
- $^{\ast 7}$ Acoustic Power and Pressure are measured using ISO 7779 standard.

SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS **CANON SINGAPORE PTE. LTD.**

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Delighting You Always

Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purposes only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.